

SFP-10DWTU-80C

10Gb/s 80km DWDM Tunable SFP Transceiver

Hot Pluggable, Duplex LC, 50GHz ITU-T-T, DWDM Tunable &APD, Single mode

Features

- Supports 9.95 to 11.3Gb/s bit rates
- Hot-Pluggable
- Duplex LC connector
- DWDM TUNABLE laser transmitter
- APD photo-detector
- 50GHz ITU-T Grid, C Band
- SMF links up to 80km
- 2-wire interface for management specifications
compliant with SFF 8472 digital diagnostic monitoring interface
- Power Supply :+3.3V
- Power consumption<2.5W
- Temperature Range: 0~ 70°C
- RoHS compliant



Applications

- Fully Tunable 50GHz DWDM SFP
- 10GBASE-ZR/ZW Ethernet
- So net OC-192/SDHSDH STM-64 ITU-T G.959.1 P1L1-2D2
- 10G Fiber channel
- DWDM Networks

Description

Ascent Optics' SFP-10DWTU-80C Small Form Factor 10Gb/s (SFP) transceivers are compliant with the current SFP Multi-Source Agreement (MSA) Specification. The high performance cooled DWDM TUNABLE transmitter and high sensitivity APD receiver provide superior performance for SONET/SDH, 10G FC and Ethernet applications up to 80km optical links.

The SFP+ Module compliants with SFF-8431, SFF-8432 and IEEE 802.3ae 10GBASE-ZR. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472.

The fully SFP compliant form factor provides hot plug ability, easy optical port upgrades and low EMI emission.

Absolute Maximum Ratings

Table 1 - Absolute Maximum Ratings

Parameter	Symbol	Min.	Typical	Max.	Unit
Storage Temperature	T _S	-40		+85	°C
Case Operating Temperature	T _A	0		70	°C
Maximum Supply Voltage	V _{cc}	-0.5		4	V
Relative Humidity	RH	0		85	%

Electrical Characteristics

SFP-10DWTU-80C: (TOP = 0 to 70 °C, VCC = 3.135 to 3.465 Volts)

Table 2- Electrical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit	Note
Supply Voltage	V _{cc}	3.135		3.465	V	
Supply Current	I _{cc}		350	450	mA	
Power Consumption	P			2.5	W	
Transmitter Section:						
Input differential impedance	R _{in}		100		Ω	1
Tx Input Single Ended DC Voltage Tolerance (Ref V _{eeT})	V	-0.3		4	V	
Differential input voltage swing	V _{in, pp}	180		700	mV	2
Transmit Disable Voltage	V _D	2		V _{cc}	V	3
Transmit Enable Voltage	V _{EN}	V _{ee}		V _{ee} +0.8	V	
Receiver Section:						
Single Ended Output Voltage Tolerance	V	-0.3		4	V	
Rx Output Diff Voltage	V _o	300		850	mV	
Rx Output Rise and Fall Time	Tr/Tf	30			ps	4
LOS Fault	V _{LOS fault}	2		V _{CCHOST}	V	5

LOS Normal	$V_{LOS\ norm}$	Vee		Vee+0.8	V	5
------------	-----------------	-----	--	---------	---	---

Note:

1. Connected directly to TX data input pins. AC coupling from pins into laser driver IC.
2. Per SFF-8431 Rev 3.0
3. Into 100 ohms differential termination.
4. 20%~80%
5. LOS is an open collector output. Should be pulled up with 4.7k – 10kΩ on the host board. Normal operation is logic 0; loss of signal is logic 1. Maximum pull-up voltage is 5.5V.

Optical Parameters

Table 3- Optical Parameters

Parameter	Symbol	Min.	Typical	Max.	Unit	Note
Transmitter Section:						
Optical Wavelength-End Of Life	λ	X-100	X	X+100	pm	
Optical Wavelength-Beginning Of Life	λ	X-25	X	X+25	pm	
Average Optical Power	P_{avg}	0		+5	dBm	1
Laser Off Power	P_{off}			-30	dBm	
Extinction Ratio	ER	6			dB	
Transmitter Dispersion Penalty	TDP			3.0	dB	2
Relative Intensity Noise	R_{in}			-128	dB/Hz	3
Optical Return Loss Tolerance		20			dB	
Receiver Section:						
Center Wavelength	λ_r	1480		1565	nm	
Los Assert	LOS_A	-40		-	dBm	
Los Dessert	LOS_D			-24	dBm	
Los Hysteresis	LOS_H	0.5			dB	
Overload	Sat	-7			dBm	5
Minimum Sensitivity	P_{min}	-	-	-24.0	dBm	2
Receiver Reflectance	R_{rx}			-12	dB	

Note:

1. Average power figures are informative only, per IEEE802.3ae.
2. TWDP figure requires the host board to be SFF-8431compliant. TWDP is calculated using the Matlab code provided in clause 68.6.6.2 of IEEE802.3ae.
3. 12dB reflection.
4. Conditions of stressed receiver tests per IEEE802.3ae. CSRS testing requires the host board to be SFF-8431 compliant.
5. Receiver overload specified in OMA and under the worst comprehensive stressed condition.

Digital Diagnostic Monitor Characteristics

Data Address	Parameter	Accuracy	Unit
96-97	Transceiver Internal Temperature	±3.0	°C
98-99	VCC3 Internal Supply Voltage	±3.0	%
100-101	Laser Bias Current	±10	%
102-103	Tx Output Power	±3.0	dB
104-105	Rx Input Power	±3.0	dB


Timing Characteristics

Table 4- Timing Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
TX_Disable Assert Time	t_off			10	us
TX_Disable Negate Time	t_on			1	ms
Time to Initialize Include Reset of TX_FAULT	t_int			300	ms
TX_FAULT from Fault to Assertion	t_fault			100	us
TX_Disable Time to Start Reset	t_reset	10			us
Receiver Loss of Signal Assert Time	T _A ,RX_LOS			100	us
Receiver Loss of Signal Deassert Time	T _d ,RX_LOS			100	us
Rate-Select Charge Time	t_ratesel			10	us
Serial ID Clock Time	t_serial-clock			100	kHz

Pin Assignment

Pin Diagram



Pin Descriptions

Table 5- Pin Descriptions

PIN #	Name	Description	Notes
1	VeeT	Module transmitter ground	1
2	Tx Fault	Module transmitter fault	2
3	Tx Disable	Transmitter Disable; Turns off transmitter laser output	3
4	SDL	2 wire serial interface data input/output (SDA)	
5	SCL	2 wire serial interface clock input (SCL)	
6	MOD-ABS	Module Absent, connect to VeeR or VeeT in the module	2
7	RS0	Rate select0, optionally control SFP+ receiver. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s	
8	LOS	Receiver Loss of Signal Indication	4
9	RS1	Rate select0, optionally control SFP+ transmitter. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s	
10	VeeR	Module receiver ground	1
11	VeeR	Module receiver ground	1
12	RD-	Receiver inverted data out put	
13	RD+	Receiver non-inverted data out put	
14	VeeR	Module receiver ground	1
15	VccR	Module receiver 3.3V supply	
16	VccT	Module transmitter 3.3V supply	
17	VeeT	Module transmitter ground	1
18	TD+	Transmitter inverted data out put	
19	TD-	Transmitter non-inverted data out put	
20	VeeT	Module transmitter ground	1

Note:

1. The module ground pins shall be isolated from the module case.
2. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.
3. This pin shall be pulled up with 4.7K-10Kohms to VccT in the module.
4. This pin is an open collector/drain output pin and shall be pulled up with 4.7K-10Kohms to Host_Vcc on the host board.

SFP Module EEPROM Information and Management

The SFP modules implement the 2-wire serial communication protocol as defined in the SFP-8472. The serial ID information of the SFP modules and Digital Diagnostic Monitor parameters can be accessed through the I²C interface at address A0h and A2h. The memory is mapped in Table 1. Detailed ID information(A0h) is listed in Table 2. And the DDM specification at address A2h. For more details of the memory map and byte definitions, please refer to the SFF-8472, "Digital Diagnostic Monitoring Interface for Optical Transceivers". The DDM parameters have been internally calibrated.

Table 1. Digital Diagnostic Memory Map (Specific Data Field Descriptions)




Table 6 -EEPROM Serial ID Memory Contents (A0h)

Data Address	Length (Byte)	Name of Length	Description and Contents
Base ID Fields			
0	1	Identifier	Type of Serial transceiver (03h=SFP)
1	1	Reserved	Extended identifier of type serial transceiver (04h)
2	1	Connector	Code of optical connector type (07=LC)
3-10	8	Transceiver	10G Base-ZR
11	1	Encoding	64B/66B

12	1	BR, Nominal	Nominal baud rate, unit of 100Mbps
13-14	2	Reserved	(0000h)
15	1	Length(9um)	Link length supported for 9/125um fiber, units of 100m
16	1	Length(50um)	Link length supported for 50/125um fiber, units of 10m
17	1	Length(62.5um)	Link length supported for 62.5/125um fiber, units of 10m
18	1	Length(Copper)	Link length supported for copper, units of meters
19	1	Reserved	
20-35	16	Vendor Name	SFP vendor name: Ascent Optics
36	1	Reserved	
37-39	3	Vendor OUI	SFP transceiver vendor OUI ID
40-55	16	Vendor PN	Part Number: "SFP-10DWTU-80C" (ASCII)
56-59	4	Vendor rev	Revision level for part number
60-62	3	Reserved	
63	1	CCID	Least significant byte of sum of data in address 0-62
Extended ID Fields			
64-65	2	Option	Indicates which optical SFP signals are implemented (001Ah = LOS, TX_FAULT, TX_DISABLE all supported)
66	1	BR, max	Upper bit rate margin, units of %
67	1	BR, min	Lower bit rate margin, units of %
68-83	16	Vendor SN	Serial number (ASCII)
84-91	8	Date code	Ascent Optics' Manufacturing date code
92-94	3	Reserved	
95	1	CCEX	Check code for the extended ID Fields (addresses 64 to 94)
Vendor Specific ID Fields			
96-127	32	Readable	Ascent Optics specific date, read only
128-255	128	Reserved	Reserved for SFF-8079


Regulatory Compliance

The SFP-10DWTU-80C complies with international Electromagnetic Compatibility (EMC) and international safety requirements and standards (see details in Table following).


Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7	Class 1(>1000 V)
Electrostatic Discharge (ESD)	IEC 61000-4-2	Compatible with standards

to the Duplex LC Receptacle	GR-1089-CORE	
Electromagnetic Interference (EMI)	FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B	Compatible with standards
Laser Eye Safety	FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2	Compatible with Class 1 laser product.

Recommended Circuit




Recommended Host Board Power Supply Circuit



Recommended High-speed Interface Circuit

Mechanical Dimensions



Order Information

Table 7- Ordering information

Part Number	Product Description
SFP-10DWTU-80C	10Gbps,DWDM SFP+ xxxx.xnm Channel 82 Tunable ,80km, 0°C to 70°C

Frequency (THZ)	Central Wavelength(nm)	ITUCh
196.15	1528.38	61.50
196.10	1528.77	61.00
196.05	1529.16	60.50
196.00	1529.55	60.00
195.95	1529.94	59.50
195.90	1530.33	59.00
195.85	1530.72	58.50
195.80	1531.12	58.00
195.75	1531.51	57.50
195.70	1531.90	57.00
195.65	1532.29	56.50
195.60	1532.68	56.00
195.55	1533.07	55.50
195.50	1533.47	55.00

195.45	1533.86	54.50
195.40	1534.25	54.00
195.35	1534.64	53.50
195.30	1535.04	53.00
195.25	1535.43	52.50
195.20	1535.82	52.00
195.15	1536.22	51.50
195.10	1536.61	51.00
195.05	1537.00	50.50
195.00	1537.40	50.00
194.95	1537.79	49.50
194.90	1538.19	49.00
194.85	1538.58	48.50
194.80	1538.98	48.00
194.75	1539.37	47.50
194.70	1539.77	47.00
194.65	1540.16	46.50
194.60	1540.56	46.00
194.55	1540.95	45.50
194.50	1541.35	45.00
194.45	1541.75	44.50
194.40	1542.14	44.00
194.35	1542.54	43.50
194.30	1542.94	43.00
194.25	1543.33	42.50
194.20	1543.73	42.00
194.15	1544.13	41.50
194.10	1544.53	41.00
194.05	1544.92	40.50
194.00	1545.32	40.00
193.95	1545.72	39.50
193.90	1546.12	39.00
193.85	1546.52	38.50
193.80	1546.92	38.00
193.75	1547.32	37.50
193.70	1547.72	37.00
193.65	1548.11	36.50

193.60	1548.51	36.00
193.55	1548.91	35.50
193.50	1549.32	35.00
193.45	1549.72	34.50
193.40	1550.12	34.00
193.35	1550.52	33.50
193.30	1550.92	33.00
193.25	1551.32	32.50
193.20	1551.72	32.00
193.15	1552.12	31.50
193.10	1552.52	31.00
193.05	1552.93	30.50
193.00	1553.33	30.00
192.95	1553.73	29.50
192.90	1554.13	29.00
192.85	1554.54	28.50
192.80	1554.94	28.00
192.75	1555.34	27.50
192.70	1555.75	27.00
192.65	1556.15	26.50
192.60	1556.55	26.00
192.55	1556.96	25.50
192.50	1557.36	25.00
192.45	1557.77	24.50
192.40	1558.17	24.00
192.35	1558.58	23.50
192.30	1558.98	23.00
192.25	1559.39	22.50
192.20	1559.79	22.00
192.15	1560.20	21.50
192.10	1560.61	21.00
192.05	1561.01	20.50
192.00	1561.42	20.00
191.95	1561.83	19.50
191.90	1562.23	19.00
191.85	1562.64	18.50
191.80	1563.05	18.00

191.75	1563.45	17.50
191.70	1563.86	17.00
191.65	1564.27	16.50
191.60	1564.68	16.00
191.55	1565.09	15.50
191.50	1565.50	15.00

Ascent Optics reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information. Edition: Apr. 2019 Published by Ascent Optics Co., Ltd. Copyright © Ascent Optics All Rights Reserved.

E-mail: sales@ascentoptics.com

Web : <http://www.ascentoptics.com>